

WS-3500M

WS-4500M



Machine Specification

Voltage (Single Phase)	100~120V AC 50/60HZ	220~240V AC 50/60HZ
Motor Rated Ampere	10A	5A
Motor Rated Power Consumption	1000W	
No-load Speed	780 RPM	
Tool Adaptor Inner Diameter	19.05mm	
Adjustable in height for Max. Stroke	100mm	
Coolant Supply	via tool Holder	
Magnet Power Consumption	38W	
Magnet Adhesion	15680N/KGF	
Magnet Dimensions	188mm x 86mm x 56mm	
Weight	14KG	
Hole-Cutting Capacity		
Annular Cutter	Out Diameter	Plate Thickness
	13-35mm	9-50mm
Twist Drill	1-13mm	

Machine Specification

Voltage (Single Phase)	100~120V AC 50/60HZ	220~240V AC 50/60HZ
Motor Rated Ampere	15A	7.5A
Motor Rated Power Consumption	1850W	
No-load Speed	650~720RPM	
Tool Adaptor Inner Diameter	19.05mm	
Adjustable in height for Max. Stroke	100mm	
Coolant Supply	via tool Holder	
Magnet Power Consumption	38W	
Magnet Adhesion	15680N/1600KGF	
Magnet Dimensions	188 x 86mm x 56mm	
Weight	15KG	
Hole-Cutting Capacity		
Annular Cutter	Out Diameter	Plate Thickness
	18-45mm	9-50mm
Drill Chuck & Twist Drill	Maximum Outer Diameter 13mm	
Special Adaptor & Twist Drill	6-12mm	